

Technical data sheet

CTB-P582C Acrylic Polymer in Primary Forms

This product is dedicated to nylon swimsuit fabric, milk silk, bamboo fiber and other special fabric printing.

Characteristics :

excellent temperature washing effect, excellent high rate, bright color and good texture.

Environmental protection:

SGS detection results of formaldehyde, APEO, PVC/ phthalate two formic acid salt, heavy metal and other four have reached the requirements of the EU

1.For Pigment Clear Paste Usage:

Pigment Clear:93-94%

Color:5-6%

CTA-F31additives:1%

2.For Pigment White Paste Usage:

Pigment White:93%

CTA-O100 additives:7%

Technological process:

Mesh:43-48T

Printing→drying→ baking(130-150%2) - finish.

Suggestions:

- 1 kinds of color, do not exceed the normal standard;
- 2, test shall ensure that the stamp is completely dry, otherwise it will affect the test results;
- 3, if not after heat treatment, to achieve the best effect of this product, recommended CT31 appropriate to extend the natural air dry time.

In verbal or written just the technical advice to show our Companies sincerity, but for our products ,the user companies still have your responsibility for test, to verify whether is suitable for the process and to use; Given the use of the products of our company process conditions are not my company control, and therefore should be fully responsible by the users themselves.